



# MOTOTRBO R2

## PORTABLE TWO-WAY RADIO

A next-level workhorse, the MOTOTRBO™ R2 marries durability and ergonomics to ensure confident, easy handling. And with superior range, configurable audio and seamless integration, the R2 is a reliable addition to an uninterrupted workday.



### KEY FEATURES

- UHF, VHF
- 64 channels
- Single-site conventional
- Extended Range Direct Mode
- Dual Capacity Direct Mode
- Transmit Interrupt
- Dual priority scan
- Quick Call II / MDC1200 capable
- Secure Enhanced Linux operating system
- Enhanced privacy
- Radio disable/enable
- Remote monitor
- Voice announcement
- Loudness up to 101 phons
- SINC+ noise suppression
- Acoustic feedback suppression
- User selectable audio profiles
- Received audio leveling
- Sleek & ergonomic form factor
- Rugged to MIL-STD 810
- IP55 (dust and water ingress protection)
- 2 programmable buttons
- Home channel reminder
- Rental timer



# SPECIFICATIONS

## GENERAL SPECIFICATIONS

Frequency	400-480 MHz	136-174 MHz
Typical RF output		
High power	4W	5W
Low power	1W	1W
Channel spacing	12.5 / 25.01 kHz <sup>1</sup>	
Channel capacity	64	
Dimension <sup>2</sup> (H x W x D) with battery		
PMNN4598 high capacity battery	4.9 x 2.2 x 1.5 in.	
PMNN4600 slim battery	4.9 x 2.2 x 1.3 in.	
Weight <sup>3</sup> with battery		
PMNN4598 high capacity battery	10.1 oz.	
PMNN4600 slim battery	9.2 oz.	
Battery life <sup>4</sup> (analog / digital)		
PMNN4598 high capacity battery	19.5 Hours / 26.5 Hours	
PMNN4600 slim battery	17 Hours / 22.5 Hours	
Power supply	7.5V (nominal)	
FCC description	AZ489FT4971	AZ489FT3852
IC description	109U-89FT4971	109U-89FT3852

<sup>1</sup>25 kHz channels not available in USA

<sup>2</sup>Dimensions at grip area

<sup>3</sup>Excludes antenna

<sup>4</sup>Typical battery life, 5/5/90 profile at maximum transmitter power. Actual observed runtimes may vary.



## TRANSMITTER SPECIFICATIONS

4FSK digital modulation	12.5 kHz Data: 7K60F1D and 7K60FXD 12.5 kHz Voice: 7K60F1E and 7K60FXE Combination: 7K60F1W
Digital protocol	ETSI TS 102 361-1, -2, -3
Conducted/radiated spurious emissions (TIA603E)	< -36 dBm for < 1 GHz ; < -30 dBm for > 1 GHz
Adjacent channel power	> 60 dB @ 12.5 kHz / > 70 dB @ 25 kHz
Frequency stability	± 0.5 ppm
Modulation limiting	± 2.5 kHz @ 12.5 kHz / ± 5.0 kHz @ 25 kHz

## RECEIVER SPECIFICATIONS

Analog sensitivity (12dB SINAD)	0.18 µV (typical)
Digital sensitivity (5% BER)	0.16 µV (typical)
Conducted/radiated spurious emissions (TIA603E)	< -57 dBm
Intermodulation (TIA603E)	> 70 dB
Adjacent channel selectivity (TIA603A)-1T	> 60 dB @ 12.5 kHz / > 70dB @ 25 kHz
Adjacent channel selectivity (TIA603E)-2T	> 55 dB @ 12.5 kHz / > 70dB @ 25 kHz
Spurious rejection (TIA603E)	> 70 dB
Frequency stability	± 0.5 ppm

## AUDIO SPECIFICATIONS

Digital vocoder type	AMBE+2
Audio response	TIA603E
Audio output power (Rated/Max)	1 W / 3 W
Audio distortion at rated audio	3% (typical)
Maximum speech loudness (ISO 532B)	101 phon
Hum and noise	-40 dB @ 12.5 kHz / -45 dB @ 25 kHz

## ENVIRONMENTAL SPECIFICATIONS

Operating temperature*	-22 °F to 140 °F
Storage temperature*	-40 °F to 185 °F
Thermal shock	Per MIL-STD 810C, D, E, F, G, H
Humidity	Per MIL-STD 810C, D, E, F, G, H
Electrostatic discharge	IEC 61000-4-2 Level 4
Dust and water intrusion	IEC60529 IP55
Salt fog	Per MIL-STD 810C/D/E/F/G/H
Packaging test	Per MIL-STD 810C/D/E/F/G/H

## MILITARY STANDARDS (MIL-STD 810)

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G		MIL-STD 810H	
	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.6	II	500.6	II
High Temp	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.6	I/A1, II/A1	501.7	I/A1, II/A1
Low Temp	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II	502.6	I, II	502.7	I, II
Temp Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.6	I-C	503.7	I-C
Solar Radiation	505.1	II	505.2	I/A1	505.3	I/A1	505.4	I/A1	505.6	I/A1	505.7	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.6	I, III	506.6	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.6	II/Aggravated	507.6	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-	509.6	-	509.7	-
Blowing Dust & Sand	510.1	I / -	510.2	I, II	510.3	I, II	510.4	I, II	510.6	I, II	510.7	I, II
Vibration	514.2	VIII/CatF, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, III/Cat3	514.5	I/Cat24, II/Cat5	514.7	I/Cat24, II/Cat5	514.8	I/Cat24, II/Cat5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.7	I, IV	516.8	I, IV

\*Temperatures listed are for radio specifications

# FEATURES

GENERAL	
Analog and digital	•
DMR standards compliant <sup>1</sup>	•
64 channels	•
2 programmable buttons	•
Pre-programmed text messaging <sup>1</sup>	•
Voice announcements	•
Home channel reminder	•
Late entry <sup>1</sup>	•
Dual priority scan	•
Nuisance channel delete	•
Secure Enhanced Linux operating system	•
TLS-PSK CPS/RM - Radio/repeater authentication	•
Rental timer	•
Internal Voice Operated Transmission (VOX)	•
Wide range of accessories	•
IP55 dust and water ingress protection	•
Rugged to MIL-STD 810	•

AUDIO	
Acoustic feedback suppressor <sup>1</sup>	•
User selectable audio profiles	•
Trill enhancement for rolling rs	•
SINC+ noise suppression	◦
Automatic gain control	•
Received audio leveling	•

SAFETY	
Basic privacy <sup>1</sup>	•
Enhanced privacy <sup>1</sup>	◦
Transmit Interrupt <sup>1,2</sup>	•
Remote monitor <sup>2</sup>	•
Radio disable / enable <sup>2</sup>	•

SYSTEMS	
Dual Capacity Direct Mode <sup>1</sup>	•
Single-site conventional	•
Extended Range Direct Mode <sup>1</sup>	•

ANALOG FEATURES	
Lone worker	•
Emergency alert	•
Analog scrambling	•
Quick Call II / MDC1200 capable	•

- Feature is standard
- Feature is optional
- <sup>1</sup> Digital feature
- <sup>2</sup> Decode



For more information, please visit [motorolasolutions.com/R2](https://motorolasolutions.com/R2)



# MOTOTRBO R2

Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. [motorolasolutions.com](https://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2023 Motorola Solutions, Inc. All rights reserved. 04-2023 [EV08]